

# Package: mschart (via r-universe)

March 27, 2025

**Type** Package

**Title** Chart Generation for 'Microsoft Word' and 'Microsoft PowerPoint' Documents

**Version** 0.4.1.002

**Description** Create native charts for 'Microsoft PowerPoint' and 'Microsoft Word' documents. These can then be edited and annotated. Functions are provided to let users create charts, modify and format their content. The chart's underlying data is automatically saved within the 'Word' document or 'PowerPoint' presentation. It extends package 'officer' that does not contain any feature for 'Microsoft' native charts production.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 2.10)

**Imports** stats, data.table, officer (>= 0.3.6), cellranger, writexl, grDevices, xml2 (>= 1.1.0), htmltools, utils, scales

**URL** <https://ardata-fr.github.io/officeverse/>,  
<https://ardata-fr.github.io/mschart/>

**BugReports** <https://github.com/ardata-fr/mschart/issues>

**RoxygenNote** 7.3.2

**Roxygen** list(markdown = TRUE)

**Suggests** tinytest, doconv

**Config/pak/sysreqs** libfontconfig1-dev libfreetype6-dev libfribidi-dev  
libharfbuzz-dev libicu-dev libjpeg-dev libpng-dev libtiff-dev  
libxml2-dev libssl-dev zlib1g-dev

**Repository** <https://janmarvin.r-universe.dev>

**RemoteUrl** <https://github.com/JanMarvin/mschart>

**RemoteRef** sec\_y\_axis

**RemoteSha** 8937c3314a6efb989a4796651ac1eafcc58ff8f2

## Contents

as_bar_stack . . . . .	2
body_add_chart . . . . .	3
browser_data . . . . .	4
browser_ts . . . . .	4
chart_ax_x . . . . .	5
chart_ax_y . . . . .	7
chart_data_fill . . . . .	9
chart_data_labels . . . . .	10
chart_data_line_style . . . . .	11
chart_data_line_width . . . . .	12
chart_data_size . . . . .	13
chart_data_smooth . . . . .	13
chart_data_stroke . . . . .	14
chart_data_symbol . . . . .	15
chart_fill_ggplot2 . . . . .	15
chart_labels . . . . .	16
chart_labels_text . . . . .	17
chart_settings . . . . .	18
chart_table . . . . .	20
mschart . . . . .	21
ms_areachart . . . . .	22
ms_barchart . . . . .	23
ms_combochart . . . . .	27
ms_linechart . . . . .	28
ms_scatterchart . . . . .	30
ph_with.ms_chart . . . . .	31
print.ms_chart . . . . .	32
set_theme . . . . .	33
theme_ggplot2 . . . . .	36
us_indus_prod . . . . .	36
<b>Index</b>	<b>38</b>

---

as_bar_stack	<i>set a barchart as a stacked barchart</i>
--------------	---

---

### Description

Apply settings to an `ms_barchart` object to produce a stacked barchart. Options are available to use percentage instead of values and to choose if bars should be vertically or horizontally drawn.

### Usage

```
as_bar_stack(x, dir = "vertical", percent = FALSE, gap_width = 50)
```

**Arguments**

x	an <code>ms_barchart</code> object
dir	the direction of the bars in the chart, value must one of "horizontal" or "vertical".
percent	should bars be in percent
gap_width	gap width between the bar for each category on a bar chart, in percent of the bar width. It can be set between 0 and 500.

**Examples**

```
library(officer)

my_bar_stack_01 <- ms_barchart(data = browser_data, x = "browser",
  y = "value", group = "serie")
my_bar_stack_01 <- as_bar_stack( my_bar_stack_01 )

my_bar_stack_02 <- ms_barchart(data = browser_data, x = "browser",
  y = "value", group = "serie")
my_bar_stack_02 <- as_bar_stack( my_bar_stack_02, percent = TRUE,
  dir = "horizontal" )

doc <- read_pptx()
doc <- add_slide(doc, layout = "Title and Content", master = "Office Theme")
doc <- ph_with(doc, my_bar_stack_02, location = ph_location_fullsize())

fileout <- tempfile(fileext = ".pptx")
print(doc, target = fileout)
```

---

body_add_chart	<i>add chart into a Word document</i>
----------------	---------------------------------------

---

**Description**

add a `ms_chart` into an `rdocx` object, the graphic will be inserted in an empty paragraph.

**Usage**

```
body_add_chart(x, chart, style = NULL, pos = "after", width = 5, height = 3)
```

**Arguments**

x	an <code>rdocx</code> object
chart	an <code>ms_chart</code> object.
style	paragraph style
pos	where to add the new element relative to the cursor, one of "after", "before", "on".
height,width	height and width in inches.

**Examples**

```
library(officer)
my_barchart <- ms_barchart(data = browser_data,
  x = "browser", y = "value", group = "serie")
my_barchart <- chart_settings( my_barchart, grouping = "stacked",
  gap_width = 50, overlap = 100 )

doc <- read_docx()
doc <- body_add_chart(doc, chart = my_barchart, style = "centered")
print(doc, target = tempfile(fileext = ".docx"))
```

---

browser_data	<i>Dummy dataset for barchart</i>
--------------	-----------------------------------

---

**Description**

A dataset containing 2 categorical and an integer variables:

**Usage**

```
data(browser_data)
```

**Format**

A data frame with 18 rows and 3 variables

**Details**

- browser web browser
- serie id of series
- value integer values

---

browser_ts	<i>Dummy dataset for barchart</i>
------------	-----------------------------------

---

**Description**

A dataset containing a date, a categorical and an integer variables:

**Usage**

```
data(browser_ts)
```

**Format**

A data frame with 36 rows and 3 variables

**Details**

- date date values
- browser web browser
- freq values in percent

---

chart_ax_x	<i>x axis settings</i>
------------	------------------------

---

**Description**

Define settings for an x axis.

**Usage**

```
chart_ax_x(
  x,
  orientation,
  crosses,
  cross_between,
  major_tick_mark,
  minor_tick_mark,
  tick_label_pos,
  display,
  num_fmt,
  rotation,
  limit_min,
  limit_max,
  position,
  second_axis = FALSE
)
```

**Arguments**

x	an ms_chart object.
orientation	axis orientation, one of 'maxMin', 'minMax'.
crosses	specifies how the axis crosses the perpendicular axis, one of 'autoZero', 'max', 'min'.
cross_between	specifies how the value axis crosses the category axis between categories, one of 'between', 'midCat'.
major_tick_mark, minor_tick_mark	tick marks position, one of 'cross', 'in', 'none', 'out'.
tick_label_pos	ticks labels position, one of 'high', 'low', 'nextTo', 'none'.
display	should the axis be displayed (a logical of length 1).
num_fmt	number formatting. See section for more details.

rotation	rotation angle. Value should be between -360 and 360.
limit_min	minimum value on the axis.
limit_max	maximum value on the axis.
position	position value that cross the other axis.
second_axis	logical to be used in ms_combochart().

### num\_fmt

All % need to be doubled, 0%% mean "a number and percent symbol".

From my actual knowledge, depending on some chart type and options, the following values are not systematically used by office chart engine; i.e. when chart pre-compute percentages, it seems using 0%% will have no effect.

- General: default value
- 0: display the number with no decimal
- 0.00: display the number with two decimals
- 0%: display as percentages
- 0.00%: display as percentages with two digits
- #,##0
- #,##0.00
- 0.00E+00
- # ?/?
- # ??/??
- mm-dd-yy
- d-mmm-yy
- d-mmm
- mmm-yy
- h:mm AM/PM
- h:mm:ss AM/PM
- h:mm
- h:mm:ss
- m/d/yy h:mm
- #,##0 ;(#,##0)
- #,##0 ;[Red](#,##0)
- #,##0.00;(#,##0.00)
- #,##0.00;[Red](#,##0.00)
- mm:ss
- [h]:mm:ss
- mmss.0
- ##0.0E+0
- @

## Illustrations

## See Also

[chart\\_ax\\_y\(\)](#), [ms\\_areachart\(\)](#), [ms\\_barchart\(\)](#), [ms\\_scatterchart\(\)](#), [ms\\_linechart\(\)](#)

## Examples

```
library(mschart)

chart_01 <- ms_linechart(
  data = us_indus_prod,
  x = "date", y = "value",
  group = "type"
)

chart_01 <- chart_ax_y(x = chart_01, limit_min = 20, limit_max = 120)
chart_01
```

---

chart\_ax\_y

*y axis settings*

---

## Description

Define settings for a y axis.

## Usage

```
chart_ax_y(
  x,
  orientation,
  crosses,
  cross_between,
  major_tick_mark,
  minor_tick_mark,
  tick_label_pos,
  display,
  num_fmt,
  rotation,
  limit_min,
  limit_max,
  position,
  second_axis = FALSE
)
```

**Arguments**

x	an ms_chart object.
orientation	axis orientation, one of 'maxMin', 'minMax'.
crosses	specifies how the axis crosses the perpendicular axis, one of 'autoZero', 'max', 'min'.
cross_between	specifies how the value axis crosses the category axis between categories, one of 'between', 'midCat'.
major_tick_mark, minor_tick_mark	tick marks position, one of 'cross', 'in', 'none', 'out'.
tick_label_pos	ticks labels position, one of 'high', 'low', 'nextTo', 'none'.
display	should the axis be displayed (a logical of length 1).
num_fmt	number formatting. See section for more details.
rotation	rotation angle. Value should be between -360 and 360.
limit_min	minimum value on the axis.
limit_max	maximum value on the axis.
position	position value that cross the other axis.
second_axis	logical to be used in ms_combochart().

**Illustrations****num\_fmt**

All % need to be doubled, 0% mean "a number and percent symbol".

From my actual knowledge, depending on some chart type and options, the following values are not systematically used by office chart engine; i.e. when chart pre-compute percentages, it seems using 0% will have no effect.

- General: default value
- 0: display the number with no decimal
- 0.00: display the number with two decimals
- 0%: display as percentages
- 0.00%: display as percentages with two digits
- #,##0
- #,##0.00
- 0.00E+00
- # ?/?
- # ??/??
- mm-dd-yy
- d-mmm-yy
- d-mmm



- mmm-yy
- h:mm AM/PM
- h:mm:ss AM/PM
- h:mm
- h:mm:ss
- m/d/yy h:mm
- #,##0 ;(#,##0)
- #,##0 ;[Red](#,##0)
- #,##0.00;(#,##0.00)
- #,##0.00;[Red](#,##0.00)
- mm:ss
- [h]:mm:ss
- mmss.0
- ##0.0E+0
- @

### See Also

[chart\\_ax\\_x\(\)](#), [ms\\_areachart\(\)](#), [ms\\_barchart\(\)](#), [ms\\_scatterchart\(\)](#), [ms\\_linechart\(\)](#)

### Examples

```
library(officer)
library(mschart)

chart_01 <- ms_linechart(
  data = us_indus_prod,
  x = "date", y = "value",
  group = "type"
)
chart_01 <- chart_settings(chart_01, style = "marker")
chart_01 <- chart_ax_x(
  x = chart_01, num_fmt = "$-fr-FR]mmm yyyy",
  limit_min = min(us_indus_prod$date),
  limit_max = as.Date("1992-01-01")
)
chart_01
```

---

chart\_data\_fill

*Modify fill colour*

---

### Description

Specify mappings from levels in the data to displayed fill colours.

**Usage**

```
chart_data_fill(x, values)
```

**Arguments**

**x** an `ms_chart` object.

**values** `character(num of series|1)`: a set of colours values to map data values to. It is a named vector, the values will be matched based on the names. If it contains only one colour, this colour will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_data\\_symbol\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
my_scatter <- ms_scatterchart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
my_scatter <- chart_data_fill(my_scatter,
  values = c(virginica = "#6FA2FF", versicolor = "#FF6161", setosa = "#81FF5B") )
```

---

chart\_data\_labels      *Modify data labels settings*

---

**Description**

Data labels show details about data series. This function indicate that data labels should be displayed. See [chart\\_labels\\_text\(\)](#) for modifying text settings associated with labels.

**Usage**

```
chart_data_labels(
  x,
  num_fmt = "General",
  position = "ctr",
  show_legend_key = FALSE,
  show_val = FALSE,
  show_cat_name = FALSE,
  show_serie_name = FALSE,
  show_percent = FALSE,
  separator = ", "
)
```

**Arguments**

x	an ms_chart object.
num_fmt	character(1): number formatting specifies number format properties which indicate how to format and render the numeric values. It can be "General", "0.00", "#,##0", "#,##0.00", "mm-dd-yy", "m/d/yy h:mm", etc.
position	character(1): it specifies the position of the data label. It should be one of 'b', 'ctr', 'inBase', 'inEnd', 'l', 'outEnd', 'r', 't'. When grouping is 'clustered', it should be one of 'ctr','inBase','inEnd','outEnd'. When grouping is 'stacked', it should be one of 'ctr','inBase','inEnd'. When grouping is 'standard', it should be one of 'b','ctr','l','r','t'.
show_legend_key	show legend key if TRUE.
show_val	show values if TRUE.
show_cat_name	show categories if TRUE.
show_serie_name	show names of series if TRUE.
show_percent	show percentages if TRUE.
separator	separator for displayed labels.

---

chart\_data\_line\_style *Modify line style*

---

**Description**

Specify mappings from levels in the data to displayed line style.

**Usage**

```
chart_data_line_style(x, values)
```

**Arguments**

x	an ms_chart object.
values	character(num of series): a set of line style values to map data values to. It is a named vector, the values will be matched based on the names. Possible values are: 'none', 'solid', 'dashed', 'dotted'. If it contains only one line style, this style will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_data\\_symbol\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
my_scatter <- ms_scatterchart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
my_scatter <- chart_data_fill(my_scatter,
  values = c(virginica = "#6FA2FF", versicolor = "#FF6161", setosa = "#81FF5B") )
my_scatter <- chart_data_stroke(my_scatter,
  values = c(virginica = "black", versicolor = "black", setosa = "black") )
my_scatter <- chart_data_symbol(my_scatter,
  values = c(virginica = "circle", versicolor = "diamond", setosa = "circle") )
my_scatter <- chart_data_line_style(my_scatter,
  values = c(virginica = "solid", versicolor = "dotted", setosa = "dashed") )
```

---

chart\_data\_line\_width *Modify line width*

---

**Description**

Specify mappings from levels in the data to displayed line width between symbols.

**Usage**

```
chart_data_line_width(x, values)
```

**Arguments**

x	an <code>ms_chart</code> object.
values	<code>double(num of series)</code> : a set of size values to map data values to. It is a named vector, the values will be matched based on the names. If it contains only one size, this size will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_data\\_symbol\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
my_scatter <- ms_scatterchart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
my_scatter <- chart_settings(my_scatter, scatterstyle = "lineMarker")
my_scatter <- chart_data_fill(my_scatter,
  values = c(virginica = "#6FA2FF", versicolor = "#FF6161", setosa = "#81FF5B") )
my_scatter <- chart_data_stroke(my_scatter,
  values = c(virginica = "black", versicolor = "black", setosa = "black") )
my_scatter <- chart_data_symbol(my_scatter,
  values = c(virginica = "circle", versicolor = "diamond", setosa = "circle") )
my_scatter <- chart_data_size(my_scatter,
  values = c(virginica = 20, versicolor = 16, setosa = 20) )
my_scatter <- chart_data_line_width(my_scatter,
  values = c(virginica = 2, versicolor = 3, setosa = 6) )
```

---

chart_data_size	<i>Modify symbol size</i>
-----------------	---------------------------

---

**Description**

Specify mappings from levels in the data to displayed size of symbols.

**Usage**

```
chart_data_size(x, values)
```

**Arguments**

x	an <code>ms_chart</code> object.
values	<code>double(num of series)</code> : a set of size values to map data values to. It is a named vector, the values will be matched based on the names. If it contains only one size, this size will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_data\\_symbol\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
my_scatter <- ms_scatterchart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
my_scatter <- chart_data_fill(my_scatter,
  values = c(virginica = "#6FA2FF", versicolor = "#FF6161", setosa = "#81FF5B") )
my_scatter <- chart_data_stroke(my_scatter,
  values = c(virginica = "black", versicolor = "black", setosa = "black") )
my_scatter <- chart_data_symbol(my_scatter,
  values = c(virginica = "circle", versicolor = "diamond", setosa = "circle") )
my_scatter <- chart_data_size(my_scatter,
  values = c(virginica = 20, versicolor = 16, setosa = 20) )
```

---

chart_data_smooth	<i>Smooth series</i>
-------------------	----------------------

---

**Description**

Specify mappings from levels in the data to smooth or not lines. This feature only applies to [ms\\_linechart\(\)](#).

**Usage**

```
chart_data_smooth(x, values)
```

**Arguments**

x an `ms_chart` object.  
 values `integer(num of series)`: a set of smooth values to map data values to. It is a named vector, the values will be matched based on the names. Possible values are 0 or 1. If it contains only one integer it will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_data\\_symbol\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
linec <- ms_linechart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
linec <- chart_data_smooth(linec,
  values = c(virginica = 0, versicolor = 0, setosa = 0) )
```

---

chart\_data\_stroke      *Modify marker stroke colour*

---

**Description**

Specify mappings from levels in the data to displayed marker stroke colours.

**Usage**

```
chart_data_stroke(x, values)
```

**Arguments**

x an `ms_chart` object.  
 values `character(num of series)`: a set of colours values to map data values to. It is a named vector, the values will be matched based on the names. If it contains only one colour, this colour will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_symbol\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
my_scatter <- ms_scatterchart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
my_scatter <- chart_data_fill(my_scatter,
  values = c(virginica = "#6FA2FF", versicolor = "#FF6161", setosa = "#81FF5B") )
my_scatter <- chart_data_stroke(my_scatter,
  values = c(virginica = "black", versicolor = "black", setosa = "black") )
```

---

chart_data_symbol	<i>Modify symbol</i>
-------------------	----------------------

---

**Description**

Specify mappings from levels in the data to displayed symbols.

**Usage**

```
chart_data_symbol(x, values)
```

**Arguments**

x	an <code>ms_chart</code> object.
values	character(num of series): a set of symbol values to map data values to. It is a named vector, the values will be matched based on the names. Possible values are: 'circle', 'dash', 'diamond', 'dot', 'none', 'plus', 'square', 'star', 'triangle', 'x', 'auto'. If it contains only one symbol, this symbol will be associated to all existing series.

**See Also**

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_labels\\_text\(\)](#)

**Examples**

```
my_scatter <- ms_scatterchart(data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species")
my_scatter <- chart_data_fill(my_scatter,
  values = c(virginica = "#6FA2FF", versicolor = "#FF6161", setosa = "#81FF5B") )
my_scatter <- chart_data_stroke(my_scatter,
  values = c(virginica = "black", versicolor = "black", setosa = "black") )
my_scatter <- chart_data_symbol(my_scatter,
  values = c(virginica = "circle", versicolor = "diamond", setosa = "circle") )
```

---

chart_fill_ggplot2	<i>Apply ggplot2 color scale</i>
--------------------	----------------------------------

---

**Description**

The default hue color scale from ggplot2.

**Usage**

```
chart_fill_ggplot2(x, stroke = TRUE)
```

**Arguments**

x a mschart object  
stroke a boolean. Apply the color scale to stroke? Defaults to TRUE.

**Value**

a mschart object

**chart\_fill\_ggplot2()****Examples**

```
p <- ms_scatterchart(  
  data = iris, x = "Sepal.Length",  
  y = "Sepal.Width", group = "Species"  
)  
  
p <- theme_ggplot2(p)  
p <- chart_fill_ggplot2(p)
```

---

chart\_labels

*Modify axis and plot labels*

---

**Description**

Add labels to a chart, labels can be specified for x axis, y axis and plot.

**Usage**

```
chart_labels(x, title = NULL, xlab = NULL, ylab = NULL)
```

**Arguments**

x an ms\_chart object.  
title, xlab, ylab  
Text to add

**Examples**

```
mylc <- ms_linechart(  
  data = browser_ts, x = "date", y = "freq",  
  group = "browser"  
)  
mylc <- chart_labels(mylc,  
  title = "my title", xlab = "my x label",  
  ylab = "my y label"  
)
```



---

chart_labels_text	<i>Modify labels font settings</i>
-------------------	------------------------------------

---

## Description

Specify mappings from levels in the data to displayed text font settings.

## Usage

```
chart_labels_text(x, values)
```

## Arguments

x	an <code>ms_chart</code> object.
values	a named list of <code>officer::fp_text()</code> objects to map data labels to. It is a named list, the values will be matched based on the names. If it contains only one <code>officer::fp_text()</code> object, it will be associated to all existing series.

## See Also

Other Series customization functions: [chart\\_data\\_fill\(\)](#), [chart\\_data\\_line\\_style\(\)](#), [chart\\_data\\_line\\_width\(\)](#), [chart\\_data\\_size\(\)](#), [chart\\_data\\_smooth\(\)](#), [chart\\_data\\_stroke\(\)](#), [chart\\_data\\_symbol\(\)](#)

## Examples

```
library(officer)

fp_text_settings <- list(
  serie1 = fp_text(font.size = 7, color = "red"),
  serie2 = fp_text(font.size = 0, color = "purple"),
  serie3 = fp_text(font.size = 19, color = "wheat")
)

barchart <- ms_barchart(
  data = browser_data,
  x = "browser", y = "value", group = "serie")
barchart <- chart_data_labels(barchart, show_val = TRUE)
barchart <- chart_labels_text( barchart,
  values = fp_text_settings )
```

---

chart_settings	<i>set chart options</i>
----------------	--------------------------

---

## Description

Set chart properties.

## Usage

```
chart_settings(x, ...)

## S3 method for class 'ms_barchart'
chart_settings(x, vary_colors, gap_width, dir, grouping, overlap, table, ...)

## S3 method for class 'ms_linechart'
chart_settings(x, vary_colors, style = "lineMarker", table, ...)

## S3 method for class 'ms_areachart'
chart_settings(
  x,
  vary_colors = FALSE,
  grouping = "standard",
  table = FALSE,
  ...
)

## S3 method for class 'ms_scatterchart'
chart_settings(x, vary_colors = FALSE, style = "marker", ...)
```

## Arguments

x	an <code>ms_chart</code> object.
...	unused parameter
vary_colors	if TRUE the data points in the single series are displayed the same color.
gap_width	A gap appears between the bar or clustered bars for each category on a bar chart. The default width for this gap is 150 percent of the bar width. It can be set between 0 and 500 percent of the bar width.
dir	the direction of the bars in the chart, value must one of "horizontal" or "vertical".
grouping	grouping for a barchart, a linechart or an area chart. must be one of "percentStacked", "clustered", "standard" or "stacked".
overlap	In a bar chart having two or more series, the bars for each category are clustered together. By default, these bars are directly adjacent to each other. The bars can be made to overlap each other or have a space between them using the overlap property. Its values range between -100 and 100, representing the percentage of the bar width by which to overlap adjacent bars. A setting of -100 creates a gap

	of a full bar width and a setting of 100 causes all the bars in a category to be superimposed. The default value is 0.
table	if TRUE set a table below the barchart.
style	Style for the linechart or scatterchart type of markers. One of 'none', 'line', 'lineMarker', 'marker', 'smooth', 'smoothMarker'.

### Methods (by class)

- `chart_settings(ms_barchart)`: barchart settings
- `chart_settings(ms_linechart)`: linechart settings
- `chart_settings(ms_areachart)`: linechart settings
- `chart_settings(ms_scatterchart)`: linechart settings

### Illustrations

### See Also

[ms\\_barchart\(\)](#), [ms\\_areachart\(\)](#), [ms\\_scatterchart\(\)](#), [ms\\_linechart\(\)](#)

### Examples

```
library(mschart)
library(officer)

chart_01 <- ms_barchart(
  data = browser_data, x = "browser",
  y = "value", group = "serie"
)
chart_01 <- chart_theme(chart_01,
  grid_major_line_x = fp_border(width = 0),
  grid_minor_line_x = fp_border(width = 0)
)

chart_02 <- chart_settings(
  x = chart_01,
  grouping = "stacked", overlap = 100
)

chart_03 <- ms_areachart(
  data = browser_ts, x = "date",
  y = "freq", group = "browser"
)
chart_03 <- chart_settings(chart_03,
  grouping = "percentStacked"
)
```

---

chart_table	<i>x table settings</i>
-------------	-------------------------

---

### Description

Define settings for an x table.

### Usage

```
chart_table(x, horizontal, vertical, outline, show_keys)
```

### Arguments

x	an ms_chart object.
horizontal	write horizontal lines in the table
vertical	write vertical lines in the table
outline	write an outline in the table
show_keys	showkeys in the table

### Examples

```
data <- data.frame(
  supp = factor(rep(c("OJ", "VC"), each = 3),
    levels = c("OJ", "VC")),
  dose = factor(rep(c("low", "medium", "high"), 2),
    levels = c("low", "medium", "high")),
  length = c(13.23, 22.7, 24.06, 7.98, 16.77, 26.14),
  label = LETTERS[1:6],
  stringsAsFactors = FALSE
)

# example chart 03 -----
chart <- ms_linechart(
  data = data, x = "dose", y = "length",
  group = "supp", labels = "label"
)
chart <- chart_settings(
  x = chart, table = TRUE
)

chart <- chart_table(chart,
  horizontal = TRUE, vertical = FALSE,
  outline = TRUE, show_keys = FALSE
)
```

---

mschart

*Chart Generation for 'Microsoft Word' and 'Microsoft PowerPoint'  
Documents*

---

## Description

It lets R users to create Microsoft Office charts from data, and then add title, legends, and annotations to the chart object.

The graph produced is a Microsoft graph, which means that it can be edited in your Microsoft software and that the underlying data are available.

The package will not allow you to make the same charts as with `ggplot2`. It allows only a subset of the charts possible with 'Office Chart'. The package is often used to industrialize graphs that are then consumed and annotated by non-R users.

The following charts are the only available from all possible MS charts:

- barcharts: `ms_barchart()`
- line charts: `ms_linechart()`
- scatter plots: `ms_scatterchart()`
- area charts: `ms_areachart()`

These functions are creating a 'chart' object, it can be customized;

- by using options specific to the chart (with `chart_settings()`),
- by changing the options related to the axes (with `chart_ax_x()` and `chart_ax_y()`),
- by changing the options related to the labels (with `chart_data_labels()`),
- by changing the colors, line widths, ... with functions
  - `chart_labels_text()`
  - `chart_data_fill()`
  - `chart_data_line_style()`
  - `chart_data_line_width()`
  - `chart_data_size()`
  - `chart_data_smooth()`
  - `chart_data_stroke()`
  - `chart_data_symbol()`
- by changing the general theme with function `chart_theme()`,
- by changing the title labels with function `chart_labels()`.

You can add a chart into a slide in PowerPoint with function `ph_with.ms_chart()`.

You can add a chart into a Word document with function `body_add_chart()`.

**Author(s)**

**Maintainer:** David Gohel <david.gohel@ardata.fr>

Other contributors:

- ArData [copyright holder]
- YouGov [funder]
- Jan Marvin Garbuszus (support for openxls2) [contributor]
- Stefan Moog <moogs@gmx.de> (support to set chart and plot area color and border) [contributor]
- Eli Daniels <eli.daniels@ardata.fr> [contributor]
- Marlon Molina (added table feature) [contributor]
- Rokas Klydzia (custom labels) [contributor]
- David Camposeco <david.camposeco.paulsen@gmail.com> (chart\_data\_smooth function) [contributor]
- Dan Joplin (fix scatter plot data structure) [contributor]

**See Also**

<https://ardata-fr.github.io/officeverse/>

---

ms\_areachart

*areachart object*

---

**Description**

Creation of an areachart object that can be inserted in a 'Microsoft' document.

Area charts can be used to plot change over time and draw attention to the total value across a trend. By showing the sum of the plotted values, an area chart also shows the relationship of parts to a whole.

**Usage**

```
ms_areachart(data, x, y, group = NULL, labels = NULL, asis = FALSE)
```

**Arguments**

data	a data.frame
x	x colname
y	y colname
group	grouping colname used to split data into series. Optional.
labels	colnames of columns to be used as labels into series. Optional. If more than a name, only the first one will be used as label, but all labels (transposed if a group is used) will be available in the Excel file associated with the chart.
asis	bool parameter defaulting to FALSE. If TRUE the data will not be modified.

**See Also**

[chart\\_settings\(\)](#), [chart\\_ax\\_x\(\)](#), [chart\\_ax\\_y\(\)](#), [chart\\_data\\_labels\(\)](#), [chart\\_theme\(\)](#), [chart\\_labels\(\)](#)

Other 'Office' chart objects: [ms\\_barchart\(\)](#), [ms\\_combochart\(\)](#), [ms\\_linechart\(\)](#), [ms\\_scatterchart\(\)](#)

**Examples**

```
library(officer)
mytheme <- mschart_theme(
  axis_title_x = fp_text(color = "red", font.size = 24, bold = TRUE),
  axis_title_y = fp_text(color = "green", font.size = 12, italic = TRUE),
  grid_major_line_y = fp_border(width = 1, color = "orange"),
  axis_ticks_y = fp_border(width = 1, color = "orange")
)

# example ac_01 -----
ac_01 <- ms_areachart(
  data = browser_ts, x = "date",
  y = "freq", group = "browser"
)
ac_01 <- chart_ax_y(ac_01, cross_between = "between", num_fmt = "General")
ac_01 <- chart_ax_x(ac_01, cross_between = "midCat", num_fmt = "m/d/yy")
ac_01 <- set_theme(ac_01, mytheme)

# example ac_02 -----
ac_02 <- chart_settings(ac_01, grouping = "percentStacked")

# example ac_03 -----
ac_03 <- chart_settings(ac_01, grouping = "percentStacked", table = TRUE)
ac_03 <- chart_table(
  ac_03,
  horizontal = FALSE, vertical = FALSE,
  outline = FALSE, show_keys = TRUE)
```

---

ms\_barchart

*barchart object*


---

**Description**

Creation of a barchart object that can be inserted in a 'Microsoft' document.

Bar charts illustrate comparisons among individual items. In a bar chart, the categories are typically organized along the vertical axis, and the values along the horizontal axis.

Consider using a bar chart when:

- The axis labels are long.
- The values that are shown are durations.

**Usage**

```
ms_barchart(data, x, y, group = NULL, labels = NULL, asis = FALSE)
```

**Arguments**

data	a data.frame
x	x colname
y	y colname
group	grouping colname used to split data into series. Optional.
labels	colnames of columns to be used as labels into series. Optional. If more than a name, only the first one will be used as label, but all labels (transposed if a group is used) will be available in the Excel file associated with the chart.
asis	bool parameter defaulting to FALSE. If TRUE the data will not be modified.

**Illustrations****See Also**

[chart\\_settings\(\)](#), [chart\\_ax\\_x\(\)](#), [chart\\_ax\\_y\(\)](#), [chart\\_data\\_labels\(\)](#), [chart\\_theme\(\)](#), [chart\\_labels\(\)](#)

Other 'Office' chart objects: [ms\\_areachart\(\)](#), [ms\\_combochart\(\)](#), [ms\\_linechart\(\)](#), [ms\\_scatterchart\(\)](#)

**Examples**

```
library(officer)
library(mschart)
library(officer)

# example chart 01 -----

chart_01 <- ms_barchart(
  data = browser_data, x = "browser",
  y = "value", group = "serie"
)
chart_01 <- chart_settings(
  x = chart_01, dir = "vertical",
  grouping = "clustered", gap_width = 50
)
chart_01 <- chart_ax_x(
  x = chart_01, cross_between = "between",
  major_tick_mark = "out"
)
chart_01 <- chart_ax_y(
  x = chart_01, cross_between = "midCat",
  major_tick_mark = "in"
)
```



```

# example chart 02 -----
dat <- data.frame(
  Species = factor(c("setosa", "versicolor", "virginica"),
    levels = c("setosa", "versicolor", "virginica")
  ),
  mean = c(5.006, 5.936, 6.588)
)
chart_02 <- ms_barchart(data = dat, x = "Species", y = "mean")
chart_02 <- chart_settings(x = chart_02, dir = "horizontal")
chart_02 <- chart_theme(x = chart_02, title_x_rot = 270, title_y_rot = 0)

# example chart 03 -----

mytheme <- mschart_theme(
  axis_title_x = fp_text(color = "gray", font.size = 20, bold = TRUE),
  axis_title_y = fp_text(color = "gray", font.size = 20, italic = TRUE),
  grid_major_line_y = fp_border(width = 1, color = "wheat"),
  axis_ticks_y = fp_border(width = 1, color = "gray")
)

chart_03 <- ms_barchart(
  data = browser_data, x = "browser",
  y = "value", group = "serie"
)
chart_03 <- chart_settings(chart_03,
  grouping = "stacked",
  gap_width = 150, overlap = 100
)
chart_03 <- chart_ax_x(chart_03,
  cross_between = "between",
  major_tick_mark = "out", minor_tick_mark = "none"
)
chart_03 <- chart_ax_y(chart_03,
  num_fmt = "0.00",
  minor_tick_mark = "none"
)
chart_03 <- set_theme(chart_03, mytheme)
chart_03 <- chart_labels(x = chart_03, title = "Things in percent")
chart_03 <- chart_data_labels(chart_03,
  position = "ctr",
  show_val = TRUE
)
chart_03 <- chart_labels_text(chart_03, fp_text(color = "white", bold = TRUE, font.size = 9))

# example chart 04 -----

dat_groups <-
  data.frame(
    cut = c(

```

```

    "Fair", "Fair", "Fair", "Fair", "Fair",
    "Fair", "Fair", "Fair", "Good", "Good", "Good", "Good", "Good",
    "Good", "Good", "Good", "Very Good", "Very Good", "Very Good",
    "Very Good", "Very Good", "Very Good", "Very Good", "Very Good",
    "Premium", "Premium", "Premium", "Premium", "Premium",
    "Premium", "Premium", "Premium", "Ideal", "Ideal", "Ideal", "Ideal",
    "Ideal", "Ideal", "Ideal", "Ideal"
  ),
  clarity = c(
    "I1", "SI2", "SI1", "VS2", "VS1", "VVS2",
    "VVS1", "IF", "I1", "SI2", "SI1", "VS2", "VS1", "VVS2", "VVS1",
    "IF", "I1", "SI2", "SI1", "VS2", "VS1", "VVS2", "VVS1", "IF",
    "I1", "SI2", "SI1", "VS2", "VS1", "VVS2", "VVS1", "IF", "I1",
    "SI2", "SI1", "VS2", "VS1", "VVS2", "VVS1", "IF"
  ),
  carat = c(
    1.065, 1.01, 0.98, 0.9, 0.77, 0.7, 0.7,
    0.47, 1.07, 1, 0.79, 0.82, 0.7, 0.505, 0.4, 0.46, 1.145, 1.01,
    0.77, 0.71, 0.7, 0.4, 0.36, 0.495, 1.11, 1.04, 0.9, 0.72, 0.7,
    0.455, 0.4, 0.36, 1.13, 1, 0.71, 0.53, 0.53, 0.44, 0.4, 0.34
  ),
  n = c(
    210L, 466L, 408L, 261L, 170L, 69L, 17L, 9L,
    96L, 1081L, 1560L, 978L, 648L, 286L, 186L, 71L, 84L, 2100L,
    3240L, 2591L, 1775L, 1235L, 789L, 268L, 205L, 2949L, 3575L, 3357L,
    1989L, 870L, 616L, 230L, 146L, 2598L, 4282L, 5071L, 3589L,
    2606L, 2047L, 1212L
  )
)
)

dat_groups$label <- sprintf(
  "carat median is %.01f",
  dat_groups$carat
)
dat_groups

text_prop <- fp_text(font.size = 11, color = "gray")

chart_04 <- ms_barchart(
  data = dat_groups, x = "cut",
  labels = "label", y = "n", group = "clarity"
)
chart_04 <- chart_settings(chart_04,
  grouping = "clustered", dir = "horizontal",
  gap_width = 0
)
chart_04 <- chart_data_labels(chart_04, position = "outEnd")
chart_04 <- chart_labels_text(chart_04, text_prop)
chart_04 <- chart_theme(chart_04, title_x_rot = 270, title_y_rot = 0)

# example chart 05 -----

dat_no_group <- data.frame(

```

```

stringsAsFactors = FALSE,
cut = c("Fair", "Good", "Very Good", "Premium", "Ideal"),
carat = c(1, 0.82, 0.71, 0.86, 0.54),
n = c(1610L, 4906L, 12082L, 13791L, 21551L),
label = c(
  "carat median is 1.0",
  "carat median is 0.8", "carat median is 0.7",
  "carat median is 0.9", "carat median is 0.5"
)
)
)
chart_05 <- ms_barchart(
  data = dat_no_group,
  x = "cut", labels = "label", y = "n"
)
chart_05 <- chart_settings(chart_05,
  grouping = "clustered"
)
)
chart_05 <- chart_data_labels(chart_05, position = "outEnd")
chart_05 <- chart_labels_text(chart_05, text_prop)

# example chart 06 -----
chart_06 <- ms_barchart(
  data = dat_no_group,
  x = "cut", labels = "label", y = "n"
)
chart_06 <- chart_settings(chart_06,
  grouping = "clustered", table = TRUE
)
)
chart_06 <- chart_data_labels(chart_06, position = "outEnd")
chart_06 <- chart_labels_text(chart_06, text_prop)

```

---

ms\_combochart

*combochart object*


---

## Description

Creation of a combochart object that can be inserted in a 'Microsoft' document.

## Usage

```
ms_combochart(...)
```

## Arguments

... mschart objects

## Details

ms\_combochart only works with mschart objects created with `asis = TRUE`.

**See Also**

[chart\\_settings\(\)](#), [chart\\_ax\\_x\(\)](#), [chart\\_ax\\_y\(\)](#), [chart\\_data\\_labels\(\)](#), [chart\\_theme\(\)](#), [chart\\_labels\(\)](#)

Other 'Office' chart objects: [ms\\_areachart\(\)](#), [ms\\_bar chart\(\)](#), [ms\\_linechart\(\)](#), [ms\\_scatterchart\(\)](#)

**Examples**

```
# example chart 01 -----

dat <- longley
dat$Year <- as.Date(paste0(dat$Year, "-01-01"))
dat$`GNP Deflator` <- dat$GNP.deflator

empl <- ms_bar chart(data = dat, x = "Year", y = c("Employed", "Unemployed"), asis = TRUE)
empl <- chart_labels(x = empl, title = "Longley's Economic Regression Data",
                    xlab = "1947 to 1962", ylab = "Employment")
empl <- chart_ax_x(x = empl, num_fmt = "yyyy")
empl <- as_bar_stack(x = empl, dir = "vertical")

gdp <- ms_linechart(data = dat, x = "Year", y = "GNP Deflator", asis = TRUE)
gdp <- chart_labels(x = gdp, ylab = "GNP implicit price deflator (1954 = 100)")
gdp <- chart_ax_y(x = gdp, second_axis = TRUE)

cb <- ms_combochart(empl, gdp)
```

---

ms\_linechart

*linechart object*


---

**Description**

Creation of a linechart object that can be inserted in a 'Microsoft' document.

In a line chart, category data is distributed evenly along the horizontal axis, and all value data is distributed evenly along the vertical axis. Line charts can show continuous data over time on an evenly scaled axis, so they're ideal for showing trends in data at equal intervals, like months and quarters.

**Usage**

```
ms_linechart(data, x, y, group = NULL, labels = NULL, asis = FALSE)
```

**Arguments**

data	a data.frame
x	x colname
y	y colname
group	grouping colname used to split data into series. Optional.

labels	colnames of columns to be used as labels into series. Optional. If more than a name, only the first one will be used as label, but all labels (transposed if a group is used) will be available in the Excel file associated with the chart.
asis	bool parameter defaulting to FALSE. If TRUE the data will not be modified.

## Illustrations

## See Also

[chart\\_settings\(\)](#), [chart\\_ax\\_x\(\)](#), [chart\\_ax\\_y\(\)](#), [chart\\_data\\_labels\(\)](#), [chart\\_theme\(\)](#), [chart\\_labels\(\)](#)

Other 'Office' chart objects: [ms\\_areachart\(\)](#), [ms\\_barchart\(\)](#), [ms\\_combochart\(\)](#), [ms\\_scatterchart\(\)](#)

## Examples

```
library(officer)
# example chart_01 -----
chart_01 <- ms_linechart(
  data = us_indus_prod,
  x = "date", y = "value",
  group = "type"
)

chart_01 <- chart_ax_x(
  x = chart_01, num_fmt = "$-fr-FR]mmm yyyy",
  limit_min = min(us_indus_prod$date), limit_max = as.Date("1992-01-01")
)

chart_01 <- chart_data_stroke(
  x = chart_01,
  values = c(adjusted = "red", unadjusted = "gray")
)

chart_01 <- chart_data_line_width(
  x = chart_01,
  values = c(adjusted = 2, unadjusted = 5)
)

chart_01 <- chart_theme(chart_01,
  grid_major_line_x = fp_border(width = 0),
  grid_minor_line_x = fp_border(width = 0)
)

# example chart_02 -----
data <- data.frame(
  supp = factor(rep(c("OJ", "VC"), each = 3), levels = c("OJ", "VC")),
  dose = factor(rep(c("low", "medium", "high"), 2), levels = c("low", "medium", "high")),
  length = c(13.23, 22.7, 24.06, 7.98, 16.77, 26.14),
  label = LETTERS[1:6],
  stringsAsFactors = FALSE
)
```

```
chart_02 <- ms_linechart(  
  data = data, x = "dose", y = "length",  
  group = "supp", labels = "label"  
)  
chart_02 <- chart_ax_y(  
  x = chart_02, cross_between = "between",  
  limit_min = 5, limit_max = 30,  
  num_fmt = "General"  
)  
chart_02 <- chart_data_labels(  
  x = chart_02, position = "1"  
)  
  
# example chart 03 -----  
chart_03 <- ms_linechart(  
  data = data, x = "dose", y = "length",  
  group = "supp", labels = "label"  
)  
chart_03 <- chart_ax_y(  
  x = chart_03, cross_between = "between",  
  limit_min = 5, limit_max = 30,  
  num_fmt = "General"  
)  
chart_03 <- chart_data_labels(  
  x = chart_03, position = "1"  
)  
  
chart_03 <- chart_settings(  
  x = chart_03, table = TRUE  
)  
  
chart_03 <- chart_table(chart_03,  
  horizontal = TRUE, vertical = FALSE,  
  outline = TRUE, show_keys = FALSE  
)
```

---

ms\_scatterchart

*scatterchart object*

---

## Description

Creation of a scatterchart object that can be inserted in a 'Microsoft' document.

## Usage

```
ms_scatterchart(data, x, y, group = NULL, labels = NULL, asis = FALSE)
```

**Arguments**

data	a data.frame
x	x colname
y	y colname
group	grouping colname used to split data into series. Optional.
labels	colnames of columns to be used as labels into series. Optional. If more than a name, only the first one will be used as label, but all labels (transposed if a group is used) will be available in the Excel file associated with the chart.
asis	bool parameter defaulting to FALSE. If TRUE the data will not be modified.

**Illustrations****See Also**

[chart\\_settings\(\)](#), [chart\\_ax\\_x\(\)](#), [chart\\_ax\\_y\(\)](#), [chart\\_data\\_labels\(\)](#), [chart\\_theme\(\)](#), [chart\\_labels\(\)](#)

Other 'Office' chart objects: [ms\\_areachart\(\)](#), [ms\\_barchart\(\)](#), [ms\\_combochart\(\)](#), [ms\\_linechart\(\)](#)

**Examples**

```
library(officer)
# example chart_01 -----
chart_01 <- ms_scatterchart(
  data = mtcars, x = "disp",
  y = "drat"
)
chart_01 <- chart_settings(chart_01, scatterstyle = "marker")

# example chart_02 -----
chart_02 <- ms_scatterchart(
  data = iris, x = "Sepal.Length",
  y = "Petal.Length", group = "Species"
)
chart_02 <- chart_settings(chart_02, scatterstyle = "marker")
```

---

ph\_with.ms\_chart

*add a MS Chart output into a PowerPoint object*

---

**Description**

produces a Microsoft Chart graphics output from R instructions and add the result in a PowerPoint document object produced by [officer::read\\_pptx\(\)](#).

**Usage**

```
## S3 method for class 'ms_chart'
ph_with(x, value, location, ...)
```

**Arguments**

x	a pptx device
value	chart object
location	a location for a placeholder.
...	Arguments to be passed to methods.

**Examples**

```
my_barchart <- ms_barchart(data = browser_data,
  x = "browser", y = "value", group = "serie")
my_barchart <- chart_settings( x = my_barchart,
  dir="vertical", grouping="clustered", gap_width = 50 )
my_barchart <- chart_ax_x( x= my_barchart,
  cross_between = 'between', major_tick_mark="out")
my_barchart <- chart_ax_y( x= my_barchart,
  cross_between = "midCat", major_tick_mark="in")

library(officer)
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content", "Office Theme")
doc <- ph_with(doc, my_barchart, location = ph_location_fullsize())

fileout <- tempfile(fileext = ".pptx")
print(doc, target = fileout)
```

---

print.ms_chart	<i>ms_chart print method</i>
----------------	------------------------------

---

**Description**

an `ms_chart` object can not be rendered in R. The default printing method will only display simple informations about the object. If argument `preview` is set to `TRUE`, a pptx file will be produced and opened with function `browseURL`.

**Usage**

```
## S3 method for class 'ms_chart'
print(x, preview = FALSE, ...)
```

**Arguments**

x	an <code>ms_chart</code> object.
preview	preview the chart in a PowerPoint document
...	unused



---

set\_theme

*set chart theme*


---

### Description

Modify chart theme with function `set_theme`.

Use `mschart_theme()` to create a chart theme.

Use `chart_theme()` to modify components of the theme of a chart.

### Usage

```
set_theme(x, value)
```

```
mschart_theme(
  axis_title = fp_text(bold = TRUE, font.size = 16),
  axis_title_x = axis_title,
  axis_title_y = axis_title,
  main_title = fp_text(bold = TRUE, font.size = 20),
  legend_text = fp_text(font.size = 14),
  table_text = fp_text(bold = FALSE, font.size = 9),
  axis_text = fp_text(),
  axis_text_x = axis_text,
  axis_text_y = axis_text,
  title_rot = 0,
  title_x_rot = 0,
  title_y_rot = 270,
  axis_ticks = fp_border(color = "#99999999"),
  axis_ticks_x = axis_ticks,
  axis_ticks_y = axis_ticks,
  grid_major_line = fp_border(color = "#99999999", style = "dashed"),
  grid_major_line_x = grid_major_line,
  grid_major_line_y = grid_major_line,
  grid_minor_line = fp_border(width = 0),
  grid_minor_line_x = grid_minor_line,
  grid_minor_line_y = grid_minor_line,
  chart_background = NULL,
  chart_border = fp_border(color = "transparent"),
  plot_background = NULL,
  plot_border = fp_border(color = "transparent"),
  date_fmt = "yyyy/mm/dd",
  str_fmt = "General",
  double_fmt = "#,##0.00",
  integer_fmt = "0",
  legend_position = "b"
)
```

```

chart_theme(
  x,
  axis_title_x,
  axis_title_y,
  main_title,
  legend_text,
  title_rot,
  title_x_rot,
  title_y_rot,
  axis_text_x,
  axis_text_y,
  axis_ticks_x,
  axis_ticks_y,
  grid_major_line_x,
  grid_major_line_y,
  grid_minor_line_x,
  grid_minor_line_y,
  chart_background,
  chart_border,
  plot_background,
  plot_border,
  date_fmt,
  str_fmt,
  double_fmt,
  integer_fmt,
  legend_position
)

```

### Arguments

<code>x</code>	an <code>ms_chart</code> object.
<code>value</code>	a <code>mschart_theme()</code> object.
<code>axis_title</code> , <code>axis_title_x</code> , <code>axis_title_y</code>	axis title formatting properties (see <code>officer::fp_text()</code> )
<code>main_title</code>	title formatting properties (see <code>officer::fp_text()</code> )
<code>legend_text</code>	legend text formatting properties (see <code>officer::fp_text()</code> )
<code>table_text</code>	table text formatting properties (see <code>officer::fp_text()</code> )
<code>axis_text</code> , <code>axis_text_x</code> , <code>axis_text_y</code>	axis text formatting properties (see <code>officer::fp_text()</code> )
<code>title_rot</code> , <code>title_x_rot</code> , <code>title_y_rot</code>	rotation angle
<code>axis_ticks</code> , <code>axis_ticks_x</code> , <code>axis_ticks_y</code>	axis ticks formatting properties (see <code>officer::fp_border()</code> )
<code>grid_major_line</code> , <code>grid_major_line_x</code> , <code>grid_major_line_y</code>	major grid lines formatting properties (see <code>officer::fp_border()</code> )
<code>grid_minor_line</code> , <code>grid_minor_line_x</code> , <code>grid_minor_line_y</code>	minor grid lines formatting properties (see <code>officer::fp_border()</code> )

```

chart_background      chart area background fill color - single character value (e.g. "#000000" or
                      "black")
chart_border          chart area border lines formatting properties (see officer::fp\_border\(\))
plot_background       plot area background fill color - single character value (e.g. "#000000" or
                      "black")
plot_border           plot area border lines formatting properties (see officer::fp\_border\(\))
date_fmt              date format
str_fmt               string or factor format
double_fmt            double format
integer_fmt           integer format
legend_position       it specifies the position of the legend. It should be one of 'b', 'tr', 'l', 'r', 't', 'n'
                      (for 'none').

```

**See Also**

[ms\\_barchart\(\)](#), [ms\\_areachart\(\)](#), [ms\\_scatterchart\(\)](#), [ms\\_linechart\(\)](#)

**Examples**

```

library(officer)
mytheme <- mschart_theme(
  axis_title = fp_text(color = "red", font.size = 24, bold = TRUE),
  grid_major_line_y = fp_border(width = 1, color = "orange"),
  axis_ticks_y = fp_border(width = .4, color = "gray")
)

my_bc <- ms_barchart(
  data = browser_data, x = "browser",
  y = "value", group = "serie"
)
my_bc <- chart_settings(my_bc,
  dir = "horizontal", grouping = "stacked",
  gap_width = 150, overlap = 100
)
my_bc <- set_theme(my_bc, mytheme)

my_bc_2 <- ms_barchart(
  data = browser_data, x = "browser",
  y = "value", group = "serie"
)
my_bc_2 <- chart_theme(my_bc_2,
  grid_major_line_y = fp_border(width = .5, color = "cyan")
)

```

---

theme_ggplot2	<i>Apply ggplot2 theme</i>
---------------	----------------------------

---

**Description**

A theme that approximates the style of `ggplot2::theme_grey`.

**Usage**

```
theme_ggplot2(x, base_size = 11, base_family = "Arial")
```

**Arguments**

x	a mschart object
base_size	base font size
base_family	font family

**Value**

a mschart object

**theme\_ggplot2()****Examples**

```
p <- ms_scatterchart(
  data = iris, x = "Sepal.Length",
  y = "Sepal.Width", group = "Species"
)

p <- theme_ggplot2(p)
p <- chart_fill_ggplot2(p)
```

---

us_indus_prod	<i>Index of US Industrial Production</i>
---------------	--

---

**Description**

Index of US industrial production (1985 = 100).

**Usage**

```
data(us_indus_prod)
```

**Format**

A data frame with 256 rows and 3 variables

**Details**

This is a transformation into simple data.frame of data USProdIndex in package 'AER'.

# Index

- \* **'Office' chart objects**
  - ms\_areachart, 22
  - ms\_barchart, 23
  - ms\_combochart, 27
  - ms\_linechart, 28
  - ms\_scatterchart, 30
- \* **Series customization functions**
  - chart\_data\_fill, 9
  - chart\_data\_line\_style, 11
  - chart\_data\_line\_width, 12
  - chart\_data\_size, 13
  - chart\_data\_smooth, 13
  - chart\_data\_stroke, 14
  - chart\_data\_symbol, 15
  - chart\_labels\_text, 17
- \* **datasets**
  - browser\_data, 4
  - browser\_ts, 4
  - us\_indus\_prod, 36
- as\_bar\_stack, 2
- body\_add\_chart, 3
- body\_add\_chart(), 21
- browser\_data, 4
- browser\_ts, 4
- chart\_ax\_x, 5
- chart\_ax\_x(), 9, 21, 23, 24, 28, 29, 31
- chart\_ax\_y, 7
- chart\_ax\_y(), 7, 21, 23, 24, 28, 29, 31
- chart\_data\_fill, 9, 11–15, 17
- chart\_data\_fill(), 21
- chart\_data\_labels, 10
- chart\_data\_labels(), 21, 23, 24, 28, 29, 31
- chart\_data\_line\_style, 10, 11, 12–15, 17
- chart\_data\_line\_style(), 21
- chart\_data\_line\_width, 10, 11, 12, 13–15, 17
- chart\_data\_line\_width(), 21
- chart\_data\_size, 10–12, 13, 14, 15, 17
- chart\_data\_size(), 21
- chart\_data\_smooth, 10–13, 13, 14, 15, 17
- chart\_data\_smooth(), 21
- chart\_data\_stroke, 10–14, 14, 15, 17
- chart\_data\_stroke(), 21
- chart\_data\_symbol, 10–14, 15, 17
- chart\_data\_symbol(), 21
- chart\_fill\_ggplot2, 15
- chart\_labels, 16
- chart\_labels(), 21, 23, 24, 28, 29, 31
- chart\_labels\_text, 10–15, 17
- chart\_labels\_text(), 10, 21
- chart\_settings, 18
- chart\_settings(), 21, 23, 24, 28, 29, 31
- chart\_table, 20
- chart\_theme (set\_theme), 33
- chart\_theme(), 21, 23, 24, 28, 29, 31
- ms\_areachart, 22, 24, 28, 29, 31
- ms\_areachart(), 7, 9, 19, 21, 35
- ms\_barchart, 3, 23, 23, 28, 29, 31
- ms\_barchart(), 7, 9, 19, 21, 35
- ms\_combochart, 23, 24, 27, 29, 31
- ms\_linechart, 23, 24, 28, 28, 31
- ms\_linechart(), 7, 9, 13, 19, 21, 35
- ms\_scatterchart, 23, 24, 28, 29, 30
- ms\_scatterchart(), 7, 9, 19, 21, 35
- mschart, 21
- mschart-package (mschart), 21
- mschart\_theme (set\_theme), 33
- mschart\_theme(), 34
- officer::fp\_border(), 34, 35
- officer::fp\_text(), 17, 34
- officer::read\_pptx(), 31
- ph\_with.ms\_chart, 31
- ph\_with.ms\_chart(), 21
- print.ms\_chart, 32

set\_theme, 33

theme\_ggplot2, 36

us\_indus\_prod, 36